



AURANZIA SPC

LOCKING SYSTEM

STONE PLASTIC COMPOSITE
FLOOR COVERINGS

SPECIFICATION:
230*1220*180*750/300*110
WEAR LAYER: 0.3MM
THICKNESS: 1.5/2.0
DPE: 1.5/2.0



ARZFLM294

230*1220*6.5/0.5+2.0 IXPE




ARZFLM252-3

230*1220*6.5/0.5+2.0 IXPE



ARZFLM252-4

230*1220*6.5/0.5+2.0 IXPE



ARZFLM248-3

230*1220*6.5/0.5+2.0 IXPE



ARZFLM012

230*1220*6.5/0.5+2.0 IXPE

AURANZIA SPC

LOCKING SYSTEM

STONE PLASTIC COMPOSITE
FLOOR COVERINGS

SPECIFICATION:
230*1220*180*750/300*110
WEAR LAYER: 0.3MM
THICKNESS: 1.5/2.0
DPE: 1.5/2.0




ARZFLM001

230*1220*6.5/0.5+2.0 IXPE




ARZFLM301-2

230*1220*6.5/0.5+2.0 IXPE



ARZFLM142

230*1220*6.5/0.5+2.0 IXPE



ARZFLM002

230*1220*6.5/0.5+2.0 IXPE



ARZFLSW101


230*1220*6.5/0.5+2.0 IXPE

AURANZIA SPC

LOCKING SYSTEM

STONE PLASTIC COMPOSITE
FLOOR COVERINGS

SPECIFICATION:
230*1220*180*750/300*110
WEAR LAYER: 0.3MM
THICKNESS: 1.5/2.0
DPE: 1.5/2.0




ARZFLSW52005-6

230*1220*6.5/0.5+2.0 IXPE



ARZFLSW120

230*1220*6.5/0.5+2.0 IXPE



ARZGE6024

305*610*6.5/0.5+2.0 IXPE



ARZLKF001A/ARZLKF001B

150*750*5.0/0.5+1.5 IXPE



ARZLKF143A/ARZLKF143B

150*750*5.0/0.5+1.5 IXPE

AURANZIA SPC

LOCKING SYSTEM

STONE PLASTIC COMPOSITE
FLOOR COVERINGS

SPECIFICATION:
230*1220*180*750/300*110
WEAR LAYER: 0.3MM
THICKNESS: 1.5/2.0
DPE: 1.5/2.0




ARZLKF052A/ARZLKF052B

150*750*5.0/0.5+1.5 IXPE




ARZLKF054A/ARZLKF054B

150*750*5.0/0.5+1.5 IXPE



ARZLKF035A/ARZLKF035B

150*750*5.0/0.5+1.5 IXPE



pasting application



environmentally friendly



locking technology



anti-slip



water resistant



mold proof



fireproof



easy to install

Environmental Protection Material/Environmentally-Friendly and Renewable/Water Proof Mouldproof.
Super wear-resistant/smoke resistance/high-tech processing special transparent wear layer.